



ADHESIVE

彬貿易公司化學黏膠製造廠 PIN TRADING COMPANY ADHESIVE MANUFACTURER

NO. 10 ADMIRALTY STREET, #01-76, NORTH LINK BLDG, SINGAPORE 757695.

TEL : 6753 9033, 6752 3383, 6269 6542 FAX : 6753 3136

BUSINESS REG. NO. : 087656/00X

GST REG. NO. : 08765600X

WORLD BRAND E-100 ADHESIVE

DESCRIPTION

World Brand E-100 Adhesive is a special adhesive for rubber, metal, wood, leather, plastics, hardboard, etc. It is suitable for use in the furniture, interior decoration, leather products, air – conditioning and shoe – making industries.

TECHNICAL SPECIFICATIONS

Type	: Polychloroprene rubber
Appearance	: Yellowish liquid
Odour	: Mixed hydrocarbon odour
Viscosity	: 3500 cps (Spindle No. 4/60 rpm at 20 °C Brookfield)
Dry Content	: 21%
Flash Point	: Less than 10 °C
Auto – Ignition Temp.:	More than 200 °C
Open Tack Time	: 45 minutes

DIRECTIONS

- Stir adhesive thoroughly before use.
- Clean and dry surfaces to be bonded.
- Apply adhesive by brush / roller in an even coating to both components.
- Allow drying up to 3 minutes before bonding.
- Bonding is made by pressing the components firmly together.

SAFETY PRECAUTIONS

- Eye contact may cause injury to eye tissues. Remove by flushing with water for at least 10 minutes. Consult a physician immediately.
- Skin contact may cause irritation and cause dermatitis. Remove with large amount of water.
- Inhalation may cause headaches and dizziness. Remove patient from contaminated area. Give artificial respiration if breathing has stopped. Consult a physician immediately.
- Ingestion may cause pulmonary edema. Induce vomiting immediately by giving two large glasses of water. Contact a physician immediately.

STORAGE

Shelf life of 12 months from date of manufacture if stored under cool and ambient temperature.

PACKAGING

Available in 1 US gallon per tin packing.

The information contained here is true and accurate to the best of our knowledge. The manufacturer makes no warranty or guarantee of results and assume no obligations or liabilities from use of this product.