

durabond®

Time Proven Quality Product

Technical
Specification
Data Sheet

****Original hard copy is available upon request.**

Issue 7 - 10
28.4.2010

Durabond CA 3073L

Base	Casein
Form	Soft paste
Colour	Yellowish to light brown
pH	7.5 - 8.5
Viscosity	40,000 - 60,000 cps @ 28°C (Brookfield RVT 7/20) <i>*Viscosity may fluctuate upon long storage.</i>
Drying time	Medium
Wet tack	Good
Residual tack	Nil
Film	The glue dries to a hazy film.
Clean up	Water
Storage life	6 months in cool dry place.
Condition	Surfaces to be glued should be free of dust, oil, grease, etc.
End use	Labelling adhesive.
Note	Do not mix with other adhesive. Practice FIFO to avoid expiry of storage life

We guarantee the consistent quality of this product which has been manufactured in accordance with ISO 9001, 14001 and OHSAS 18001 guidelines. The product has been found suitable for the applications and uses listed above. For other uses and application methods we strongly suggest to contact our technical support staff.

The information contained herein is true and accurate to the best of our knowledge. Revertex Finewaters Sdn. Bhd. make no warranty or guarantee of results and assumes no obligations or liabilities from the use of any products or processes mentioned herein. This publication is not to be taken as a licence to operate under or recommendation to infringe upon, any patents.



REVERTEX FINEWATERS SDN. BHD. (Company No. 265645-P)

P.O.Box 152, 41710 Klang, Selangor Darul Ehsan, Malaysia

Tel: 603-33428625 (Hunting Line) Fax: 603-33420658

Email: rfw@rfw.com.my

<http://www.revertexfinewaters.com>

