




ADHESIVE

Material Safety Data Sheet

Product name: WB800

Version No: 001 28-April-2008

1. Chemical Product and Company Identification

| | | | | | | | | | |
|---|---|---------------|----------|-------------|----------|-------------------|----------|----------------------------|----------|
| <p>Trade Name: World Brand Adhesive No. 800</p> <p>Company : Pin Trading Company Adhesive Manufacturer 10, Admiralty Street, #01-76, North Link Building, Singapore 757695</p> <p>Information Telephone Number: 65- 62696542 Emergency Contact: Drug & Poison Contact Center Emergency Telephone Number: 65-64239119</p> <p>UN Hazard Class: 3 IMO UN Number: 1294 Product Code: 5386</p> | <p>NFPA</p> <div style="text-align: center;">  </div> <table border="1" style="margin-left: auto; margin-right: auto;"> <tr> <td style="background-color: blue; color: white;">Health</td> <td style="text-align: center;">2</td> </tr> <tr> <td style="background-color: red; color: white;">Fire</td> <td style="text-align: center;">3</td> </tr> <tr> <td style="background-color: yellow; color: black;">Reactivity</td> <td style="text-align: center;">0</td> </tr> <tr> <td style="background-color: white; color: black;">Personal Protection</td> <td style="text-align: center;">H</td> </tr> </table> | Health | 2 | Fire | 3 | Reactivity | 0 | Personal Protection | H |
| Health | 2 | | | | | | | | |
| Fire | 3 | | | | | | | | |
| Reactivity | 0 | | | | | | | | |
| Personal Protection | H | | | | | | | | |

2. Composition and Information on Ingredients

| Composition | Cas # | % by weight |
|-----------------|------------|-------------|
| Zinc Oxide | 1314-13-2 | 0.6% |
| Magnesium Oxide | 1309-48-4 | 0.6% |
| Phenolic Resin | 9003-35-4 | 5.6% |
| Polychloroprene | 9010-98-8 | 16.0% |
| Ethyl Acetate | 141-78-6 | 16.0% |
| SBP 80/100 | N/A | 16.0% |
| Hexane | 64742-49-0 | 12.8% |
| Toluene | 108-88-3 | 32.1% |

Toxicological Data on Ingredients: Toluene: ORAL (LD50): Acute: 636 mg/kg [Rat]. DERMAL (LD50): Acute: 14100 mg/kg [Rabbit]. VAPOR (LC50): Acute: 49000 mg/m 4 hours [Rat]. 440 ppm 24 hours [Mouse]. Ethyl Acetate: ORAL (LD50): Acute: 5620 mg/kg [Rat]. Hexane: ORAL (LD50): Acute: 49 ml/kg [Rat].

3. Hazards Identification

Potential Acute Health Effects: Hazardous in case of skin contact (irritant), of eye contact (irritant), of ingestion, of inhalation.

Potential Chronic Health Effects:

CARCINOGENIC EFFECTS: Not available.

MUTAGENIC EFFECTS: Not available.

TERATOGENIC EFFECTS: Not available.

DEVELOPMENTAL TOXICITY: Not available.

The substance may be toxic to blood, kidneys, the nervous system, liver, brain, central nervous system (CNS).

Repeated or prolonged exposure to the substance can produce target organs damage.

4. First Aid Measures

Eye Contact:

Check for and remove any contact lenses. In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention.

Skin Contact:

In case of contact, immediately flush skin with plenty of water. Cover the irritated skin with an emollient. Remove contaminated clothing and shoes. Wash clothing before reuse. Thoroughly clean shoes before reuse. Get medical attention.



ADHESIVE

Material Safety Data Sheet

Product name: WB800

Serious Skin Contact:

Wash with a disinfectant soap and cover the contaminated skin with an anti-bacterial cream. Seek medical attention.

Inhalation:

If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.

Serious Inhalation:

Evacuate the victim to a safe area as soon as possible. Loosen tight clothing such as a collar, tie, belt or waistband. If breathing is difficult, administer oxygen. If the victim is not breathing, perform mouth-to-mouth resuscitation. **WARNING:** It may be hazardous to the person providing aid to give mouth-to-mouth resuscitation when the inhaled material is toxic, infectious or corrosive. Seek medical attention.

Ingestion:

Do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. If large quantities of this material are swallowed, call a physician immediately. Loosen tight clothing such as a collar, tie, belt or waistband.

Serious Ingestion: Not available.

5. Fire and Explosion Data

Flammability of the Product: Flammable

Auto-Ignition Temperature: More than 200 deg C.

Flash Points: Less than 10 deg C.

Flammable Limits: Not available.

Products of Combustion: These products are carbon oxides (CO, CO₂).

Fire Hazards in Presence of Various Substances: Flammable in presence of open flames and sparks, of heat. Non-flammable in presence of shocks.

Explosion Hazards in Presence of Various Substances:

Risks of explosion of the product in presence of mechanical impact: Not available.

Risks of explosion of the product in presence of static discharge: Not available.

Fire Fighting Media and Instructions:

Flammable liquid, insoluble in water.

SMALL FIRE: Use DRY chemical powder.

LARGE FIRE: Use water spray or fog.

Special Remarks on Fire Hazards: Not available.

Special Remarks on Explosion Hazards: Toluene forms explosive reaction with

1,3-dichloro-5,5-dimethyl-2,4-imidazolididione; dinitrogen tetraoxide; concentrated nitric acid, sulfuric acid + nitric acid; N₂O₄; AgClO₄; BrF₃; Uranium hexafluoride; sulfur dichloride. Also forms an explosive mixture with tetranitromethane.

6. Accidental Release Measures

Small Spill:

Absorb with an inert material and put the spilled material in an appropriate waste disposal.

Large Spill:



ADHESIVE

Material Safety Data Sheet

Product name: WB800

Toxic flammable liquid, insoluble or very slightly soluble in water. Keep away from heat. Keep away from sources of ignition. Stop leak if without risk. Absorb with DRY earth, sand or other non-combustible material. Do not get water inside container. Do not touch spilled material. Prevent entry into sewers, basements or confined areas; dike if needed. Call for assistance on disposal. Be careful that the product is not present at a concentration level above TLV. Check TLV on the MSDS and with local authorities.

7. Handling and Storage

Precautions: Keep away from heat. Keep away from sources of ignition. Ground all equipment containing material. Do not ingest. Do not breathe gas/fumes/ vapor/spray. Wear suitable protective clothing. In case of insufficient ventilation, wear suitable respiratory equipment. If ingested, seek medical advice immediately and show the container or the label. Avoid contact with skin and eyes. Keep away from incompatibles such as oxidizing agents.

Storage: Store in a segregated and approved area. Keep container in a cool, well-ventilated area. Keep container tightly closed and sealed until ready for use. Avoid all possible sources of ignition (spark or flame).

8. Exposure Controls/Personal Protection

Engineering Controls:

Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective threshold limit value. Ensure that eyewash stations and safety showers are proximal to the work-station location.

Personal Protection:

Splash goggles. Lab coat. Vapor respirator. Be sure to use an approved/certified respirator or equivalent. Gloves.

Personal Protection in Case of a Large Spill:

Splash goggles. Full suit. Vapor respirator. Boots. Gloves. A self contained breathing apparatus should be used to avoid inhalation of the product. Suggested protective clothing might not be sufficient; consult a specialist BEFORE handling this product.

Exposure Limits:

TWA: 200 STEL: 500 CEIL: 300 (ppm) from OSHA (PEL) [United States]

TWA: 50 (ppm) from ACGIH (TLV) [United States] SKIN

TWA: 100 STEL: 150 from NIOSH [United States]

TWA: 375 STEL: 560 (mg/m³) from NIOSH [United States]

Consult local authorities for acceptable exposure limits.

9. Physical and Chemical Properties

Physical state and appearance: Yellow viscous liquid with mixed hydrocarbon odour.

Odor: Mixed hydrocarbon odour.

Taste: Not available.

Molecular Weight: Not available.

Color: Yellow

pH (1% soln/water): Not available.

Boiling Point: 70 deg C.

Melting Point: Not available.



ADHESIVE

Material Safety Data Sheet

Product name: WB800

Critical Temperature: Not available.

Specific Gravity: 0.929 (Water = 1)

Vapor Pressure: 3.8kPa (@25 deg C)

Vapor Density: 3.1 (Air=1).

Volatility: Not available.

Odor Threshold: Not available.

Water/Oil Dist. Coeff.: Not available.

Ionicity (in Water): Not available.

Dispersion Properties: Not available.

Solubility:

Soluble in diethyl ether, acetone.

Practically insoluble in cold water.

Soluble in ethanol, benzene, chloroform, glacial acetic acid, carbon disulfide.

10. Stability and Reactivity Data

Stability: The product is stable.

Instability Temperature: Not available.

Conditions of Instability: Heat, ignition sources (flames, sparks, static), incompatible materials

Incompatibility with various substances: Reactive with oxidizing agents.

Corrosivity: Non-corrosive in presence of glass.

Special Remarks on Reactivity:

Incompatible with strong oxidizers, silver perchlorate, sodium difluoride, Tetranitromethane, Uranium Hexafluoride.

Frozen Bromine Trifluoride reacts violently with Toluene at -80 deg C.

Reacts chemically with nitrogen oxides, or halogens to form nitrotoluene, nitrobenzene, and nitrophenol and halogenated products, respectively.

Special Remarks on Corrosivity: Not available.

Polymerization: Will not occur.

11. Toxicological Information

Routes of Entry: Absorbed through skin. Eye contact. Inhalation. Ingestion.

Toxicity to Animals:

WARNING: THE LC50 VALUES HEREUNDER ARE ESTIMATED ON THE BASIS OF A 4-HOUR EXPOSURE.

Acute oral toxicity (LD50): 636 mg/kg [Rat].

Acute dermal toxicity (LD50): 14100 mg/kg [Rabbit].

Acute toxicity of the vapor (LC50): 440 24 hours [Mouse].



ADHESIVE

Material Safety Data Sheet

Product name: WB800

Chronic Effects on Humans: CARCINOGENIC EFFECTS: A4 (Not classifiable for human or animal.) by ACGIH, 3 (Not classifiable for human.) by IARC.

May cause damage to the following organs: blood, kidneys, the nervous system, liver, brain, central nervous system (CNS).

Other Toxic Effects on Humans: Hazardous in case of skin contact (irritant), of ingestion, of inhalation. Slightly hazardous in case of skin contact (permeator).

Special Remarks on Toxicity to Animals: Lowest Published Lethal Dose:

LDL [Human] - Route: Oral; Dose: 50 mg/kg

LCL [Rabbit] - Route: Inhalation; Dose: 55000 ppm/40min

Special Remarks on Chronic Effects on Humans: Not available.

Special Remarks on other Toxic Effects on Humans:

Skin: Causes mild to moderate skin irritation. It can be absorbed to some extent through the skin.

Eyes: Causes mild to moderate eye irritation with a burning sensation. Splash contact with eyes also causes conjunctivitis, blepharospasm, corneal edema, corneal abrasions. This usually resolves in 2 days.

Inhalation: Inhalation of vapor may cause respiratory tract irritation causing coughing and wheezing, and nasal discharge. Inhalation of high concentrations may affect behavior and cause central nervous system effects characterized by nausea, headache, dizziness, tremors, restlessness, lightheadedness, exhilaration, memory loss, insomnia, impaired reaction time, drowsiness, ataxia, hallucinations, somnolence, muscle contraction or spasticity, unconsciousness and coma. Inhalation of high concentration of vapor may also affect the cardiovascular system (rapid heart beat, heart palpitations, increased or decreased blood pressure, dysrhythmia,), respiration (acute pulmonary edema, respiratory depression, apnea, asphyxia), cause vision disturbances and dilated pupils, and cause loss of appetite.

Ingestion: Aspiration hazard. Aspiration of Toluene into the lungs may cause chemical pneumonitis. May cause irritation of the digestive tract with nausea, vomiting, pain. May have effects similar to that of acute inhalation.

Chronic Potential Health Effects:

Inhalation and Ingestion: Prolonged or repeated exposure via inhalation may cause central nervous system and cardiovascular symptoms similar to that of acute inhalation and ingestion as well liver damage/failure, kidney damage/failure (with hematuria, proteinuria, oliguria, renal tubular acidosis), brain damage, weight loss, blood (pigmented or nucleated red blood cells, changes in white blood cell count), bone marrow changes, electrolyte imbalances (Hypokalemia, Hypophosphatemia), severe, muscle weakness and Rhabdomyolysis.

Skin: Repeated or prolonged skin contact may cause defatting dermatitis.

12. Ecological Information

Ecotoxicity: Ecotoxicity in water (LC50): 313 mg/l 48 hours [Daphnia (daphnia)]. 17 mg/l 24 hours [Fish (Blue Gill)]. 13 mg/l 96 hours [Fish (Blue Gill)]. 56 mg/l 24 hours [Fish (Fathead minnow)]. 34 mg/l 96 hours [Fish (Fathead minnow)]. 56.8 ppm any hours [Fish (Goldfish)].

BOD5 and COD: Not available.

Products of Biodegradation:

Possibly hazardous short term degradation products are not likely. However, long term degradation products may arise.

Toxicity of the Products of Biodegradation: The products of degradation of calcium sulfate are less toxic than the product itself.

Special Remarks on the Products of Biodegradation: Not available.

13. Disposal Considerations

Waste Disposal:

Waste must be disposed of in accordance with federal, state and local environmental control regulations.



ADHESIVE

Material Safety Data Sheet

Product name: WB800

14. Transport Information

DOT Classification: CLASS 3: Flammable liquid.

Identification: Toluene UNNA: 1294 PG: II

Special Provisions for Transport: Not applicable.

15. Other Regulatory Information

Federal and State Regulations:

California prop. 65: This product contains the following ingredients for which the State of California has found to cause cancer, birth defects or other reproductive harm, which would require a warning under the statute: Toluene

California prop. 65 (no significant risk level): Toluene: 7 mg/day (value)

California prop. 65 (acceptable daily intake level): Toluene: 7 mg/day (value)

California prop. 65: This product contains the following ingredients for which the State of California has found to cause birth defects which would require a warning under the statute: Toluene

Connecticut hazardous material survey.: Toluene

Illinois toxic substances disclosure to employee act: Toluene

California Director's List of Hazardous Substances.: Toluene

TSCA 8(b) inventory: Toluene

TSCA 8(d) H and S data reporting: Toluene: Effective date: 10/04/82; Sunset Date: 10/0/92

SARA 313 toxic chemical notification and release reporting: Toluene

CERCLA: Hazardous substances.: Toluene: 1000 lbs. (453.6 kg)

Other Regulations:

OSHA: Hazardous by definition of Hazard Communication Standard (29 CFR 1910.1200).

EINECS: This product is on the European Inventory of Existing Commercial Chemical Substances.

Other Classifications:

WHMIS (Canada):

CLASS B-2: Flammable liquid with a flash point lower than 37.8°C (100°F).

CLASS D-2A: Material causing other toxic effects (VERY TOXIC).

DSCL (EEC):

R11- Highly flammable.

R20- Harmful by inhalation.

S16- Keep away from sources of ignition – No smoking.

S25- Avoid contact with eyes.

S29- Do not empty into drains.

S33- Take precautionary measures against static discharges.

HMIS (U.S.A.):

Health Hazard: 2

Fire Hazard: 3

Reactivity: 0

Personal Protection: h

National Fire Protection Association (U.S.A.):

Health: 2

Flammability: 3

Reactivity: 0

Specific hazard:



ADHESIVE

Material Safety Data Sheet

Product name: WB800

Protective Equipment:

Gloves.

Lab coat.

Vapor respirator. Be sure to use an approved/certified respirator or equivalent. Wear appropriate respirator when ventilation is inadequate.

Splash goggles.

16. Other Information

References: Not available.

Other Special Considerations: Not available.

Created: 28/04/2008

Last Updated: 28/04/2008

The information above is believed to be accurate and represents the best information currently available to us. However, we make no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigations to determine the suitability of the information for their particular purposes. In no event shall ScienceLab.com be liable for any claims, losses, or damages of any third party or for lost profits or any special, indirect, incidental, consequential or exemplary damages, howsoever arising, even if AMLAB has been advised of the possibility of such damages.