

durabond®

Time Proven Quality Product

Technical
Specification
Data Sheet

****Original hard copy is available upon request.**

Issue 5 - 10

30.3.2010

Durabond PA 1045

Base	Polyvinyl Acetate
Form	Emulsion
Colour	White
pH	6.5 - 7.5
Viscosity	22,500 - 32,500 cps @ 28°C (Brookfield RVT 6/20)
Drying time	Medium
Wet tack	Good
Film	The glue dries to a hazy film.
Clean up	Wet - water Dry - mechanical scrapping
Storage life	1 year in cool dry place.
Adherend	Surfaces to be glued should be free of dust, oil, grease, etc.
End use	<ol style="list-style-type: none">1. Bookbinding : This formulation offers the advantage of strength over a wide temperature range, flexibility, adhesion to difficult substrate and adaptability to variety of machine conditions. Its properties made it very desirable for padding, casing-in and end-paper gluing.2. General purpose/ Paper to paper.
Note	Do not mix with other adhesives.

We guarantee the consistent quality of this product which has been manufactured in accordance with ISO 9001, 14001 and OHSAS 18001 guidelines. The product has been found suitable for the applications and uses listed above. For other uses and application methods we strongly suggest to contact our technical support staff.

The information contained herein is true and accurate to the best of our knowledge. Revertex Finewaters Sdn. Bhd. make no warranty or guarantee of results and assumes no obligations or liabilities from the use of any products or processes mentioned herein. This publication is not to be taken as a licence to operate under or recommendation to infringe upon, any patents.



REVERTEX FINEWATERS SDN. BHD. (Company No. 265645-P)

P.O.Box 152, 41710 Klang, Selangor Darul Ehsan, Malaysia

Tel: 603-33428625 (Hunting Line) Fax: 603-33420658

Email: rfw@rfw.com.my

<http://www.revertexfinewaters.com>

