

Technical Specification Data Sheet

**Original hard copy is available upon request.

Issue 5 - 10 28.4.2010

Durabond PA 117

Base Polyvinyl Acetate

Form Emulsion
Colour White

pH 2.0 - 3.5

Viscosity 13,000 - 16,000 cps @ 28°C

(Brookfield RVT 5/20)

*Viscosity may fluctuate upon long storage.

Wet tack Good

Film The adhesive dries to a hazy film.

Diluent Water - Only when necessary as adhesive bond weakens

progressively with dilution.

Clean up Wet - water

Dry - mechanical scrapping

Storage life 6 months in cool dry place.

Inflammability Non-flammable

Adherend Surfaces must be free of dust, oil, grease, etc for maximum bond performance.

Bond Strength Satisfies the requirements for a Durability Class 3 Adhesive:

BS EN 204: 2001 Certification from FIRA is available on request.

End use 1 component wood working adhesive with high moisture resistance.

No staining with H₂O₂ whitening bleach

Note Do not mix with other adhesives.

No formaldehyde is intentionally added during the manufacturing process,

we do not expect it to be present in this product.

We guarantee the consistent quality of this product which has been manufactured in accordance with ISO 9001, 14001 and OHSAS 18001 guidelines. The product has been found suitable for the applications and uses listed above. For other uses and application methods we strongly suggest to contact our technical support staff.

The information contained herein is true and accurate to the best of our knowledge. Revertex Finewaters Sdn. Bhd. make no warranty or guarantee of results and assumes no obligations or liabilities from the use of any products or processes mentioned herein. This publicatio is not to be taken as a licence to operate under or recommendation to infringe upon, any patents.







