

# **durabond®**

Time Proven Quality Product

Technical  
Specification  
Data Sheet

**\*\*Original hard copy is available upon request.**

Issue 5 - 10

28.4.2010

## **Durabond PC 8823HV**

<b>Base</b>	Ethylene Vinyl Acetate Copolymer
<b>Form</b>	Emulsion
<b>Colour</b>	White
<b>pH</b>	4.0 - 6.5
<b>Viscosity</b>	6,000 - 10,000 cps @ 28°C (Brookfield RVT 5/20)
<b>Drying time</b>	Fast
<b>Wet tack</b>	Good
<b>Residual tack</b>	Nil
<b>Film</b>	The glue dries to a light hazy film.
<b>Clean up</b>	Wet - water Dry - mechanical scrapping
<b>Storage life</b>	1 year in cool dry place.
<b>Inflammability</b>	Non-flammable
<b>Adherend</b>	Surfaces to be glued should be free of dust, oil, grease, etc.
<b>End use</b>	Pressure sensitive adhesive for non porous substrates lamination such as PVC/ PU leather/ fabric surface.
<b>Note</b>	Do not mix with other adhesives.

*We guarantee the consistent quality of this product which has been manufactured in accordance with ISO 9001, 14001 and OHSAS 18001 guidelines. The product has been found suitable for the applications and uses listed above. For other uses and application methods we strongly suggest to contact our technical support staff.*

The information contained herein is true and accurate to the best of our knowledge. Revertex Finewaters Sdn. Bhd. make no warranty or guarantee of results and assumes no obligations or liabilities from the use of any products or processes mentioned herein. This publication is not to be taken as a licence to operate under or recommendation to infringe upon, any patents.



**REVERTEX FINEWATERS SDN. BHD.** (Company No. 265645-P)

P.O.Box 152, 41710 Klang, Selangor Darul Ehsan, Malaysia

Tel: 603-33428625 (Hunting Line) Fax: 603-33420658

Email: rfw@rfw.com.my

<http://www.revertexfinewaters.com>

